

THE AW300 SERIES - AWNING



STANDARD FEATURES

- 3 1/4" Frame Depth
- Custom Sizing To The Nearest 1/4"
- Beveled Exterior Sash Profile For Design
- Replacement, New Construction Or Integral
- 2 1/2" Flat Casing
- Euro White, Almond, Bronze, Black, 2-Tone Lami Black
- Fusion Welded Frame & Sashes
- Maintenance Free Multi-Chambered Vinyl Profiles
- Plated Heavy Duty Hardware
- Multi Point Locking System
- Dual Locking Handles
- Fold-In Operator
- 12" Dual Scissor Operator
- Heavy Duty Weatherstripping For Air & Water Performance
- Snap-In Glazing Beads For Easy Glass Replacement
- 7/8" Overall Insulated Glass Unit
- High Performance Warm Edge Spacer System
- Standard Full Screen - Roll Formed Aluminum Frame
- Fiberglass Screen Mesh
- Accessory Groves For Easy Zero Degree Mulling
- Continuous Frame For Muller Units
- AAMA Gold Label Standard
- Limited Lifetime Warranty!



WINDOW + DOOR
TOP 100
MANUFACTURERS



AW300
AVAILABLE OPTIONS

NFRC RATINGS

GLASS CONFIGURATION	FOAM	U-FACTOR	SHGC	VT
CLEAR (SS)/AIR/CLEAR (SS)	NO	0.41	0.52/0.47	0.54/0.48
CLEAR (DS)/AIR/CLEAR (DS)	NO	0.41	0.51/0.46	0.53/0.48
E270 LOWE (SS)/ARG90/CLEAR (SS)	NO	0.27	0.24/0.22	0.46/0.41
E270 LOWE (DS)/ARG90/CLEAR (DS)	NO	0.27	0.24/0.22	0.45/0.41
E270 LOWE (SS)/ARG90/CLEAR (SS)	YES	0.26	0.24/0.22	0.46/0.41
E270 LOWE (DS)/ARG90/CLEAR (DS)	YES	0.26	0.24/0.22	0.45/0.41
E270 LOWE (DS)/ARG90/CS73P (DS)	YES	0.23	0.23/0.21	0.42/0.38
E180 LOWE (DS)/ARG90/CS73P (DS)	YES	0.23	0.40/0.36	0.48/0.43

MAKE SIZES

MIN. WIDTH	18"
MAX. WIDTH	48"
MULLED UNIT REQUIRED W > 48"	
MIN. HEIGHT	14"
MAX. HEIGHT	48"
TRANSOM REQUIRED H > 48"	
MIN. EGRESS W	N.A.
MIN. EGRESS H	N.A.

AAMA RATINGS

Performance	R-PG40
Air	<.01 @ 1.57 PSF
Water Resistance	6.06 PSF
Uniform Structural Load	60.15 PSF
Uniform Design Load	40 PSF
Forced Entry	Grade 10
Status	Gold Label