

THE PW330 SERIES - PICTURE



STANDARD FEATURES

- 3 1/4" Frame Depth
- Custom Sizing To The Nearest 1/4"
- Replacement, New Construction Or Integral 2 1/2" Flat Casing
- Euro White, Almond, Bronze, Black, 2-Tone Lami Black
- Double Strength Glass By Default In Units Over 101 U.I.
- Fusion Welded Frame & Sashes
- Trimline Profiles For Larger Glass Space
- Maintenance Free Multi-Chambered Vinyl Profiles
- Snap-In Glazing Beads For Easy Glass Replacement
- 7/8" Overall Insulated Glass Unit
- High Performance Warm Edge Spacer System
- Accessory Grooves For Easy Zero Degree Mulling
- Continuous Frame For Mullled Units
- Architectural Shapes & Bends Available
- AAMA Gold Label Standard
- Limited Lifetime Warranty!



Two-Tone Laminated Exterior Black Shown



WINDOW + DOOR
TOP 100
MANUFACTURERS



NFRC RATINGS

GLASS CONFIGURATION	FOAM	U-FACTOR	SHGC	VT
CLEAR (SS)/AIR/CLEAR (SS)	NO	0.47	0.69/0.62	0.72/0.64
CLEAR (DS)/AIR/CLEAR (DS)	NO	0.47	0.67/0.61	0.71/0.64
E270 LOWE (SS)/ARG90/CLEAR (SS)	NO	0.28	0.32/0.29	0.61/0.55
E270 LOWE (DS)/ARG90/CLEAR (DS)	NO	0.27	0.32/0.29	0.60/0.54
E270 LOWE (SS)/ARG90/CLEAR (SS)	YES	0.26	0.32/0.29	0.61/0.55
E270 LOWE (DS)/ARG90/CLEAR (DS)	YES	0.26	0.32/0.29	0.60/0.54
E270 LOWE (DS)/ARG90/CS73P (DS)	YES	0.22	0.30/0.27	0.56/0.51
E180 LOWE (DS)/ARG90/CS73P (DS)	YES	0.22	0.53/0.47	0.64/0.57

MAKE SIZES

MIN. WIDTH	14"
MAX. WIDTH	96"
MULLED UNIT REQUIRED W > 96"	
MIN. HEIGHT	14"
MAX. HEIGHT	96"
TRANSOM REQUIRED H > 96"	
MIN. EGRESS W	N.A.
MIN. EGRESS H	N.A.

AAMA RATINGS

Performance	R-PG60
Air	<.03 @ 1.57 PSF
Water Resistance	12 PSF
Uniform Structural Load	90 PSF
Uniform Design Load	60 PSF
Forced Entry	Grade 10
Status	Gold Label

PW330
AVAILABLE OPTIONS