

THE 4000 SERIES - DOUBLE HUNG



# STANDARD FEATURES

- Replacement 3 1/4" Frame Depth
- Custom Sizing To The Nearest 1/4"
- Euro White, Almond, Bronze, Black, 2-Tone Lami Black
- Fusion Welded Frame & Sashes
- Maintenance Free Multi-Chambered Vinyl Profiles
- Built-In Water Weeping System
- Constant Steel Force Coil Balances
- Two Premium Night Latches
- One Piece Sloped Sill - No Weep Hole Covers!
- Positive Action Cam Lock & Keeper
- Dual Locks For Windows Wider Than 24"
- Heavy Duty Weatherstripping For Air & Water Performance
- Tilt-In & Removable Sashes For Easy Cleaning
- Snap-In Glazing Beads For Easy Glass Replacement
- 7/8" Overall Insulated Glass Unit
- High Performance Warm Edge Spacer System
- Fully Extruded Integral Heavy Duty Lift Handles
- Built In Jamb Adjusters For Easy Installation
- Pre-Drilled Pilot Holes For Easy Installation
- Head Expander & Adjustable Sill Angle
- Standard Half Screen - Roll Formed Aluminum Frame
- Fiberglass Screen Mesh
- Metal Reinforced Meeting Railings
- Accessory Groves For Easy Zero Degree Mulling
- Continuous Frame For Muller Units
- AAMA Gold Label Standard
- Limited Lifetime Warranty!



\*Optional Fiberglass Reinforcement & Foam Shown



WINDOW + DOOR  
TOP 100  
MANUFACTURERS



**DH4000**  
**AVAILABLE OPTIONS**

GLASS CONFIGURATION	NFRC RATINGS			
	FOAM	U-FACTOR	SHGC	VT
CG70 (SS)/ARG90/CLEAR (SS)	NO	0.28	0.26/0.24	0.52/0.46
CG70 (DS)/ARG90/CLEAR (DS)	NO	0.28	0.26/0.24	0.51/0.46
CG70 (SS)/ARG90/CLEAR (SS)	YES	0.26	0.26/0.24	0.52/0.46
CG70 (DS)/ARG90/CLEAR (DS)	YES	0.26	0.26/0.24	0.51/0.46
E270 (DS)/ARG90/CS73P (DS)	YES	0.23	0.26/0.23	0.50/0.44
E180 (DS)/ARG90/CS73P (DS)	YES	0.24	0.49/0.41	0.50/0.44
CG70 (DS)/ARG90/LAMI 1/4" CLR	NO	0.27/0.27	0.26/0.24	0.50/0.45
CG70 (DS)/ARG90/LAMI 1/4" CLR	YES	0.26/0.26	0.28/0.25	0.51/0.46

MAKE SIZES	
MIN. WIDTH	14"
MAX. WIDTH	48"
MULLED UNIT REQUIRED W > 48"	
MIN. HEIGHT	28"
MAX. HEIGHT	90"
TRANSOM REQUIRED H > 90"	
MIN. EGRESS W	37.25"
MIN. EGRESS H	63"

AAMA RATINGS	
Performance	R-PG35
With Metal Reinforcement	R-PG50
Air	<.22 @ 1.57 PSF
Water Resistance	5.25 PSF
Uniform Structural Load	50.25 PSF
Uniform Design Load	35 PSF
Forced Entry	Grade 10
Status	Gold Label